

US006483866B1

# (12) United States Patent

Suzuki

(10) Patent No.:

US 6,483,866 B1

(45) Date of Patent:

\*Nov. 19, 2002

# (54) MULTI-STATION TRANSMISSION METHOD AND RECEIVER FOR INVERSE TRANSFORMING TWO PSEUDOORTHOGONAL TRANSMISSION SEQUENCES USED FOR METRIC CALCULATION AND BASE STATION SELECTION BASED THEREON

(75) Inventor: Hiroshi Suzuki, Yokosuka (JP)

(73) Assignee: NTT Mobile Communications Network Inc., Tokyo (JP)

(\*) Notice:

This patent issued on a continued prosecution application filed under 37 CFR 1.53(d), and is subject to the twenty year patent term provisions of 35 U.S.C. 154(a)(2).

Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 168 days.

(21) Appl. No.: 08/374,692

(22) PCT Filed: Oct. 11, 1994

(86) PCT No.: PCT/JP94/01692

§ 371 (c)(1), (2), (4) Date: **Jan. 24, 1995** 

(87) PCT Pub. No.: WO95/10924
PCT Pub. Date: Apr. 20, 1995

(30) Foreign Application Priority Data

Oct. 12, 1993 (JP) ...... 5-254112

(51) Int. Cl.<sup>7</sup> ...... H04J 11/00; H04B 7/216

### (56) References Cited

## U.S. PATENT DOCUMENTS

|           | 7 |   | إ مهاجة كمليك | 459 ,                     |
|-----------|---|---|---------------|---------------------------|
| 3,815,028 | Α | ٠ | 6/1974        | Rakow 375/341             |
| 4,884,272 | Α | ٠ | 11/1989       | McConnell 371/43          |
| 5,109,390 | Α | ٠ | 4/1992        | Gilhousen et al 375/1     |
| 5,179,571 | Α |   |               | Schilling                 |
| 5,202,903 | Α | ٠ | 4/1993        | Okanoue 375/347           |
| 5,267,261 | Α | ٠ | 11/1993       | Blakeney, II et al 375/1  |
| 5,289,499 | Α | ٠ | 2/1994        | Weerackody 375/206        |
| 5,351,274 | Α | ٠ | 9/1994        | Chonnakeshu et al 375/347 |
| 5,450,453 | Α | ٠ | 9/1995        | Frank 375/200             |
|           |   |   |               |                           |

#### FOREIGN PATENT DOCUMENTS

WO WO 83/01878 5/1983

# OTHER PUBLICATIONS

TIA/EIA Interim Standard—95, Mobile Station—Based Station Compatibility Standard for Dual Mode Wideband Spread Spectrum Cellular System. Chapter 7, Jul. 1993.\*

\* cited by examiner

Primary Examiner—William Luther (74) Attorney, Agent, or Firm—Connolly Bove Lodge & Hutz LLP

#### ABSTRACT

In a multi-station transmission method and receiver using training signals, a forward signal is transformed in a signal transformation part to two pseudo-orthogonal transmission signal sequences, which are framed in base stations of two adjacent zones and augmented with orthogonal training signals, thereafter being transmitted over the same channels. A signal received by a receiver of a mobile station is separated, by a signal separation part using the training signals corresponding to the respective base stations, into signal sequences received from the respective base stations. The received signal sequences are subjected to an inverse transformation by inverse transformation circuits to obtain two transmitted signal sequences, and one of these signal sequences which has a larger metric is selectively outputted.

#### 8 Claims, 4 Drawing Sheets

eti siriğbunduş elektrikli

